

# TB系列 防水接线盒

## TB Series Plastic Enclosure




Out of the plastic boxes which are selling at present, It's ability and working efficiency, the competitive power is much higher with the low price same as the level of steel box. The products were added the electromagnetic interference(EMI) and prevent substance of the static electricity, and the strong point was given to the relevant mechanical protection of electricity, electron and etc.

Temperature range: -40 to +120°C      ABS: Acrylonitrile Butadiene Styrene      PC: Poly Carbonate

Dimension(允许误差 ± 1mm)	RoHS	CE	IP66	BAUART GEBÜHRT TYPE APPROVED	UL	防水防尘等级	IP66
						温度范围	-40°C~+80°C

Size	产品型号 Product model (Plastic latch+hinge type)										底板型号 Plate Model		金属底板规格 Plate Size	
	W	H	D	D1	D2	ABS	PC/ABS	PC	PC	Metal(金属)	M1	M2		
						盖:灰色ABS 盒体:灰色ABS Cover:Grey ABS Body:Grey ABS	盖:透明PC 盒体:灰色ABS Cover:Transparent PC Body:Grey ABS	盖:灰色PC 盒体:灰色PC Cover:Grey PC Body:Grey PC	盖:透明PC 盒体:灰色PC Cover:Transparent PC Body:Grey PC					
<b>NEW</b>	78 x 113 x 55	73.5	108.5	55	43	15	TB-AG-0711	TB-AT-0711	TB-PG-0711	TB-PT-0711	DS-0711	65	98	
	80 x 120 x 54	83	124	54	43	15	TB-AG-0812	TB-AT-0812	TB-PG-0812	TB-PT-0812	DS-0812	75	115	
	100 x 100 x 54	104	104	54	43	15	TB-AG-1010	TB-AT-1010	TB-PG-1010	TB-PT-1010	DS-1010	95	95	
<b>NEW</b>	100 x 200 x 70	104.5	204	70	57.5	15.5	TB-AG-1020	TB-AT-1020	TB-PG-1020	TB-PT-1020	DS-1020	95	195	
	110 x 150 x 72	113	153	72	52	24	TB-AG-1115	TB-AT-1115	TB-PG-1115	TB-PT-1115	DS-1115	104	144	
	140 x 190 x 76	144	194	70	54	25	TB-AG-1419	TB-AT-1419	TB-PG-1419	TB-PT-1419	DS-1419	126	176	
<b>NEW</b>	150 x 150 x 70	154.5	154.5	70	57.5	15.5	TB-AG-1515	TB-AT-1515	TB-PG-1515	TB-PT-1515	DS-2010	145	145	
	190 x 240 x 95	195	250	95	70	28	TB-AG-1924	TB-AT-1924	TB-PG-1924	TB-PT-1924	DS-1924	176	230	
	190 x 240 x 165	195	250	165	70	98	TB-AG-1924-1	TB-AT-1924-1	TB-PG-1924-1	TB-PT-1924-1	DS-1924-1	176	230	
	220 x 300 x 125	230	310	125	79	50	TB-AG-2230	TB-AT-2230	TB-PG-2230	TB-PT-2230	DS-2230	210	290	
	220 x 300 x 185	220	300	185	79	110	TB-AG-2230-1	TB-AT-2230-1	TB-PG-2230-1	TB-PT-2230-1	DS-2230	210	290	
	300 x 380 x 125	310	390	125	78	50	TB-AG-3038	TB-AT-3038	TB-PG-3038	TB-PT-3038	DS-3038	290	370	
	300 x 380 x 185	310	390	185	78	110	TB-AG-3038-1	TB-AT-3038-1	TB-PG-3038-1	TB-PT-3038-1	DS-3038	290	370	

### TB接线盒塑料盒



安装底板



TB-AG-0812~TB-AG-1115金属螺丝



TB-AG-1419~TB-AG-3038塑料螺丝



可90° 开启

## TB Series Plastic Enclosure

Dimension(允許誤差 ± 1mm)



CE IP66



防水防尘等级 IP66  
温度范围 -40°C+80°C

